

VetPro® VDX

Digital Dental Radiography
Sensor System



Build your successful companion
animal dental practice with
VetPro® VDX — exceptional digital
dental diagnostic images in seconds.



VetPro® VDX

Advanced digital dental imaging made easy.

Capture diagnostic digital images with extraordinary detail and clarity.



The durable design of the new VetPro® VDX sensor takes the worry out of digital image capture.

- Cable is Kevlar® reinforced for exceptional durability
- Hermetically sealed, waterproof design means no problems during routine cleaning
- Advanced CMOS technology delivers outstanding image quality
- High speed USB connection captures images 37% faster
- Rounded corners means easier positioning in tight spaces for better capture of roots
- Factory repair service is available if your sensor or cable become damaged

VetPro® VDX delivers fast, clean images for diagnosis and client education. Superior soft-tissue visualization; crown and root definition and low noise produce the quality digital images you need in your practice.

No-Hassle installation: VetPro® VDX uses the latest USB technology. Simply connect the USB cable to your PC; use the quick calibration flash drive to prepare your sensor, and the system is ready to take high quality digital images.



Imaging Software

Use your VetPro® VDX System with our own easy to use imaging software. Look and formatting is familiar and easy to learn. Acquire, enhance and store images with ease. Our software features canine and feline tooth templates organized using the Triadan System, is DICOM compliant and able to work with leading practice management systems and PACS servers.

Specifications

Dimensions

Size 1 (film size equivalent)
37 mm x 24 mm x 6 mm

Size 2 (film size equivalent)
43 mm x 30 mm x 6 mm

Active Area

Size 1 (film size equivalent)
30 mm x 20 mm

Size 2 (film size equivalent)
36 mm x 26 mm

Number of Pixels

Size 1 (film size equivalent)
1580 lines x 1050 pixels

Size 2 (film size equivalent)
1896 lines x 1368 pixels

Pixel Size

19 µm x 19 µm

Theoretical Resolution

26 lp/mm

Grey Shades

65,000

Connection Type

High speed USB

Sensor Cable Length

3 meters

Warranty

2 years

Model Numbers

XSVS-01 Size 1, 3 meter cable

XSVS-02 Size 2, 3 meter cable

Buying a complete imaging system? Add extra sensors using the model numbers below
XSVN-01 Size 1, .9 meter cable
XSVN-02 Size 2, .9 meter cable



facebook.com/MidmarkAnimalHealth

